

## pH ELECTRODE Model CA 11



### TECHNICAL SPECIFICATIONS:

1.	pH Range	:	0 - 14
2.	Operating Temperature	:	-5 to 70°C
3.	Slope	:	59 $\pm$ 3 mV (95-105%) at 25°C
4.	Zero Point	:	pH 7
5.	Asymmetry Potential	:	0 $\pm$ 25 mV
6.	Response Time	:	<10 sec for 95% response from pH 7.00 to pH 4.01
7.	Stability	:	<3 mV drift/24 hours in pH7 buffer
8.	Glass Membrane Impedance	:	<200 M $\Omega$ at 25°C
9.	Diaphragm	:	Ceramic
10.	No. of Junctions	:	Single
11.	Reference System	:	Ag/ AgCl
12.	pH Storage Solution (in bottle)	:	Saturated KCl/ TOSHCON storage solution
13.	Reference Electrolyte	:	KCl
14.	Shape of Membrane	:	Spherical
15.	Diameter	:	12 mm
16.	Shaft Length	:	120 mm
17.	Shaft Material	:	Glass
18.	Connector type	:	Cap with BNC with Low-Noise Coaxial Cable or S7 or any other connector requested.
19.	Suitability	:	Suitable/ compatible with mostly all make instruments.

### OTHER INDUSTRY:

Pharma, Petrochemical, Swimming Pools, Aquarium, Electroplating, Food, Chemical, Fertilizer, Dairy, Oil, Drinking Water, Ground Water, Waste Water

### OTHER APPLICATIONS:

Extreme pH (Acidic), Extreme pH (Alkali), Narrow Vessel/ Semi Micro, Low Ionic/ Ultrapure, Oil/ Water Emulsion, HF, Low Temp. (-30°C), High Temp. (135°C), Steam Sterilisable

---

**TOSHNIWAL INSTRUMENTS MANUFACTURING PVT. LTD.,**

P.O. Gagwana - 305023, Distt. Ajmer (Raj.) INDIA

Phone: +91-145-2971131/2/3; Mobile: +91-9829112345

Email: [info@toshcon.com](mailto:info@toshcon.com), [support@toshcon.com](mailto:support@toshcon.com); Website: [www.toshcon.com](http://www.toshcon.com)

REGD OFFICE: 401, Manish Chamber, Sonawala Cross Lane, Goregaon (E), MUMBAI - 400 063