

## CONDUCTIVITY CELL/ ELECTRODE TCC1 & TCC01



### SPECIFICATIONS

<b>Model :</b>	<b>TCC1</b>
<b>K (Cell constant)</b>	1.0
<b>Range</b>	50.0 $\mu$ S to 100 mS
<b>Material</b>	Pure Platinum Foils
<b>Body Material</b>	Borosilicate Glass
<b>Temp. Range</b>	0 - 50°C
<b>Max. Pressure</b>	Approx. 40 psi
<b>Length</b>	150 mm
<b>Dia.</b>	12 mm
<b>Connector</b>	BNC Connector

<b>Model :</b>	<b>TCC01</b>
<b>K (Cell constant)</b>	0.1
<b>Range</b>	0.50 $\mu$ S to 100 $\mu$ S
<b>Material</b>	Pure Platinum Foils
<b>Body Material</b>	Borosilicate Glass
<b>Temp. Range</b>	0 - 50°C
<b>Max. Pressure</b>	Approx. 40 psi
<b>Length</b>	150 mm
<b>Dia.</b>	12 mm
<b>Connector</b>	BNC Connector

- \* The same electrodes can also be used for measuring Resistivity/ TDS/ Salinity
- \* Conductivity Cell of K=10 on request

---

**TOSHNIWAL INSTRUMENTS MANUFACTURING PVT. LTD.,**

P.O. Gagwana - 305023, Distt. Ajmer (Raj.) INDIA

Phone: +91-145-2971131/2/3; Mobile: +91-9829112345

Email: [info@toshcon.com](mailto:info@toshcon.com), [support@toshcon.com](mailto:support@toshcon.com); Website: [www.toshcon.com](http://www.toshcon.com)

REGD OFFICE: 401, Manish Chamber, Sonawala Cross Lane, Goregaon (E), MUMBAI - 400 063