

ELECTRO CHEMISTRY & WATER

ANALYSIS INSTRUMENTS

BENCHTOP MULTI-PARAMETER INSTRUMENTS "BLACK PEARL 17 SERIES" MODEL TC-17



- "30 Sec" measurement
- "6 Click" Calibration
- European technology



TC-17	
Conductivity	0 2000 mS/cm
Resistivity	0 200 MΩ.cm
Salinity	0 70 ppt
TDS	0 100 g/l
Temperature	-5 +105°C

The leader in **Conductivity, TDS, Salinity, Resistivity, Temperature** measurement just got better with a completely advanced & highly sophisticated new range of Benchtop Instruments with a European collaboration for the following Parameters:

These Instruments have a list of numerous salient features which make this range incomparable & highly advanced when compared with most of the other meters available in the market & some of which are as follows

Conductivity • TDS • Salinity • Resistivity • Temp.

- Direct Printer
- 3 Year warranty on the Instruments
- Data logging of up to 12000+ values including Temperature

- Stability Indicator
- GLP Report on LCD Screen
- White backlight for better viewing
- Robust dust & splash-proof cabinet

Manufactured by:

TOSHNIWAL INSTRUMENTS MANUFACTURING PVT. LTD.

P.O. Gagwana – 305023, Distt. Ajmer (Raj.) INDIA., Phone : +91-145-2971131/2/3

Customer Care: +91-9829 112345 Email: info@toshcon.com / support@toshcon.com

REGD. OFFICE: 401, Manish Chamber, Sonawala Cross Lane, Goregaon (E), Mumbai-400063

Web : www.toshcon.com

COMMON FEATURES

Conductivity

Multi-point (1...3) calibration for more linearity.
Extended conductivity range; to measure the full range from 0.01 $\mu\text{S}/\text{cm}$ to 2000 $\mu\text{S}/\text{cm}$ requires 3 electrodes: 0.1, 1 and 10 cm^{-1} .

Selectable reference temperature: 20° or 25°C.
Automatic cell constant determination with any of three preprogrammed standards (0.01, 0.1 or 1M KCL).

Temperature

Reads temperatures with 0.1°C resolution.
Manual or automatic temperature compensation.
Calibrates temperature probe for quality measurements.

Inputs

1 BNC inputs for Conductivity
1 Corresponding reference inputs.
1 Corresponding temperature inputs.
1 Voltage DC input for e.g. a mains adaptor.

Outputs

Rs232 interface for connection to a printer

Display

Bright LCD screen for better readability.
White backlight for better viewing.
Stability indicator prompts the user when readings should be taken.
Shows a GLP report on the LCD screen.
The interactive LCD screen provides step by step instructions in the language of your choice (English, Dutch, French, German).

Data-logging

Storage memory for 12,000+ values including temperature

*Cabinet:

Robust dust and splash-proof cabinet.

*Special features:

Communication with a printer using RS232.

Standard Supply

Meter + Mains Adaptor + Electrode Stand + ATC + Instruction Manual + Test Certificate +Warranty Card

CONDUCTIVITY	
Range	0...2000 $\mu\text{S}/\text{cm}$
Resolution	0.01 $\mu\text{S}/\text{cm}$
Accuracy	0.5% F.S. Of Range
Calibration	1...3 Point
Standards	0.01/0.1/1m KCL 3 User Specified
Cell Constant	0.1/10 cm^{-1} ± 30%
Temperature Compensation	-5...+105°C
Reference Temperature	20° Or 25°C
Temperature Coefficient	Natural Waters (En27888)
Range Lock	✓
Capacitive Compensation	✓
RESISTIVITY	
Range	0...200 M Ω cm
Resolution	1 M Ω cm
SALINITY	
Range	0...70 ppt
Resolution	0.1 ppt
TDS	
Range	0 ... 100 g/l
Resolution	0.1 mg/l
TEMPERATURE	
Range	-5...+105°C
Resolution	0.1°C
Accuracy	0.3°C
Calibration	1 point
INPUTS	
Conductivity	
Temperature	White RC Plug, for Pt1000
CALIBRATION	
Reminder	0...999 h
GLP	✓
DISPLAY	
LCD	240x64 pixels each
White Backlight	✓
Hold Function	✓
Selectable Resolution	✓
Interface with computer	✓
RS 232	
Baud Rate	1200...115200 b/s
DATA-LOGGING	
Values	12000+ °C/date/time
Manul or Timed	✓
Interval	1...9999 s
SECURITY	
Identification number	✓
Password protection	✓
AMBIENT CONDITIONS	
Temperature	0...40°C
Humidity	0...95%, non-condensing
POWER SUPPLY	
Mains	210...250 VAC, 50/60 Hz
Low Voltage	9...15 VDC
DIMENSIONS	
WxDxH	18x13x5/3 cm
WEIGHT METER	
	400 gm

Manufactured by:

TOSHNIWAL INSTRUMENTS MANUFACTURING PVT. LTD.

P.O. Gagwana – 305023, Distt. Ajmer (Raj.) INDIA., Phone : +91-145-2971131/2/3

Customer Care: +91-9829 112345 Email: info@toshcon.com / support@toshcon.com

REGD. OFFICE: 401, Manish Chamber, Sonawala Cross Lane, Goregaon (E), Mumbai-400063

Web : www.toshcon.com

BLACK PEARL TC 17