

SENSABLACK VOLT

GLASS BODY ORP ELECTRODE

INDIAS FIRST ELECTROCHEMISTRY SENSOR WITH:

- Unique " IOREF" reference for "stability"
- Ergonomic "2 tone Cap" design



TECHNICAL SPECIFICATIONS:

ORP range	±2000 mV
Operating Temperature	-5 to 80°C
Reference impedance	< 50 KΩ at 25° C
Diaphragm	Ceramic
No. of Junctions	Single
Reference System	Ag/ AgCl
pH Storage Solution	Saturated KCl
Reference Electrolyte	KCl
Shape of Membrane	Platinum Disc
Diameter	12 mm
Shaft Length	120 mm
Shaft Material	Glass
Connector type	Cap/TC* with BNC with Low-Noise Coaxial Cable or S8 or Variopin or any other connector requested.
Suitability	Suitable/ compatible with mostly all make instruments.

ORDERING CODE

Cap / Connector

Cap	-	2 tone
S8	-	S8

Sensablaclk Volt -X-X-X

Cable Length for Cap

Electrode:

1 Mtrs.	-	1
2 Mtrs.	-	2
3 Mtrs.	-	3

Sensablaclk Volt-X-X-X

Temp. Compensator:

Without	-	-
Pt100	-	T
Pt1000	-	1T

Sensablaclk Volt-X-X-X

OTHER INDUSTRY:

Pharma, Petrochemical, Swimming Pools, Aquarium, Electroplating, Food, Chemical, Fertilizer, Dairy, Oil, Drinking Water, Ground Water, Waste Water

OTHER APPLICATIONS:

Ultrapure, Oil/ Water Emulsion, HF

Manufactured by:

TOSHNIWAL INSTRUMENTS MANUFACTURING PVT. LTD.,

P.O. Gagwana - 305023, Distt. Ajmer (Raj.) INDIA, PHONE: +91-145-2971131/2//3

CUSTOMER CARE: +91-9829112345

EMAIL: info@toshcon.com, support@toshcon.com

REGD OFFICE: 401, Manish Chamber, Sonawala Cross Lane, Goregaon (E) Mumbai-400 063

WEBSITE: www.toshcon.com

SENSABLACK VOLT