

pH ELECTRODE

Model CABRJ

(Glass Body, Gel filled)



TECHNICAL SPECIFICATIONS:

1.	pH Range	:	0 - 14
2.	Operating Temperature	:	0 to 80°C
3.	Slope	:	59 ±3 mV (95-105%) at 25°C
4.	Zero Point	:	pH 7
5.	Asymmetry Potential	:	0±25 mV
6.	Glass Membrane Impedance	:	< 500 MΩ at 25°C
7.	Membrane Glass	:	Brown
8.	Temperature Compensation	:	Pt100/ Pt1000/ 30K NTC
9.	Diaphragm	:	Ceramic
10.	No. of Junctions	:	Single
11.	Reference System	:	SREF+
12.	Reference Electrolyte	:	HGel+
13.	pH Storage Solution	:	Saturated KCl/ TOSHCON storage solution
14.	Shape of Membrane	:	Spherical
15.	Diameter	:	12 mm
16.	Shaft Length	:	120 mm
17.	Shaft Material	:	Glass
18.	Connector type	:	Cap with BNC with Low-Noise Coaxial Cable or S7 or S8 (PG 13.5) or Variopin
19.	Suitability	:	Suitable/ compatible with mostly all make instruments.

ORDERING CODE

CABRJ- X - X - X

Cap/ Connector:	Temp. Compensator:	Cable Length for Cap Electrode:
Cap - -	Without - -	0.75 Mtr. - -
PG 13.5 - S8	Pt100 - T	1 Mtr. - 1
S7 - S7	Pt1000 - 1T	2 Mts. - 2
Variopin - V	30K NTC - 3T	3 Mtrs. - 3

Imp.: With S7 Connector no Temp. Compensator can be selected.

OTHER INDUSTRY:

Pharma, Petrochemical, Swimming Pools, Aquarium, Electroplating, Food, Chemical, Fertilizer, Dairy, Oil, Drinking Water, Ground Water, Waste Water

OTHER APPLICATIONS:

Extreme pH (Acidic), Extreme pH (Alkali), Narrow Vessel/ Semi Micro, Low Ionic/ Ultrapure, Oil/ Water Emulsion, HF, Low Temp. (-30°C), High Temp. (135°C), Steam Sterilisable

Sold & Serviced by:

TOSHNIWAL INSTRUMENTS MANUFACTURING PVT. LTD.,

P.O.Gagwana - 305023, Distt: Ajmer (Raj.) INDIA

CIN: U65990MH1979PTC021556

Phone: +91-145-2971131/ 2/ 3 E-mail: info@toshcon.com Website: www.toshcon.com

REGD OFFICE: 401, Manish Chamber, Sonawala Cross Lane, Goregaon (E), MUMBAI - 400 063